## Lambourn Orange Multi Stock







Ibstock Code:3035Type:StockFacing Description:SandfacedDry Brick Weight (kg):2.5kgPack Quantity:500Packaging (standard):Banded (plastic)Factory:Parkhouse <b>Technical Specification (to BS EN 771-1)</b> Brick Dimensions (L x W x H mm):215x102x65Size Tolerances Mean & Range:T2 R1Configuration:Single FrogVoids (%):7-12Compressive Strength (N/mm <sup>2</sup> ):15	
Facing Description:SandfacedPack Quantity:2.5kgPack Quantity:500Packaging (standard):Banded (plastic)Factory:ParkhouseFactory:ParkhouseDrechnical Specification (to BS EN 771-1)215x102x65Size Tolerances Mean & Range:T2 R1Configuration:Single FrogVoids (%):7-12	
Dry Brick Weight (kg):2.5kgPack Quantity:500Packaging (standard):Banded (plastic)Factory:ParkhouseTechnical Specification (to BS EN 771-1)ParkhouseBrick Dimensions (L x W x H mm):215x102x65Size Tolerances Mean & Range:T2 R1Configuration:Single FrogVoids (%):7-12	
Pack Quantity:500Packaging (standard):Banded (plastic)Factory:ParkhouseTechnical Specification (to BS EN 771-1)ParkhouseBrick Dimensions (L x W x H mm):215x102x65Size Tolerances Mean & Range:T2 R1Configuration:Single FrogVoids (%):7-12	
Packaging (standard):Banded (plastic)Factory:ParkhouseTechnical Specification (to BS EN 771-1)215x102x65Brick Dimensions (L x W x H mm):215x102x65Size Tolerances Mean & Range:T2 R1Configuration:Single FrogVoids (%):7-12	
Factory:ParkhouseTechnical Specification (to BS EN 771-1)215x102x65Brick Dimensions (L x W x H mm):215x102x65Size Tolerances Mean & Range:T2 R1Configuration:Single FrogVoids (%):7-12	
Technical Specification (to BS EN 771-1)Brick Dimensions (L x W x H mm):215x102x65Size Tolerances Mean & Range:T2 R1Configuration:Single FrogVoids (%):7-12	
Brick Dimensions (L x W x H mm):215x102x65Size Tolerances Mean & Range:T2 R1Configuration:Single FrogVoids (%):7-12	
Size Tolerances Mean & Range:T2 R1Configuration:Single FrogVoids (%):7-12	
Configuration:Single FrogVoids (%):7-12	
Voids (%): 7-12	
Compressive Strength (N/mm <sup>2</sup> ):	
Active Soluble Salts: S2	
Water Absorption (% weight): 13	
Durability: F2	
Gross Dry Density (Sound Insulation) (Kg/m <sup>3</sup> ): 1700	
Equivalent Thermal Conductivity "K" value 5% Exposed: Refer to Ibstock	
Initial Rate of Absorption (Suction Rate) (Kg/m <sup>2</sup> /min): Refer to Ibstock	
EAN: 5036335037515	

17/01/2020